

JUL 31 2006

Amendments to the Claims:

1. (Currently amended) A method for shifting the phase of a pseudorandom noise (PN) code, the method comprising:
 - accepting a PN code with a first phase;
 - determining a first time interval;
 - selecting a plurality of phase-shifting masks stored in a memory at a first time in response to the first time interval;
 - shifting the PN code first phase with each phase-shifting mask from the plurality of selected phase-shifting masks; and
 - generating a PN code with a second phase, offset by the first time interval from the PN code first phase.
2. (Original) The method of claim 1 wherein determining a first time interval includes accepting a first time interval from among a plurality of first time intervals.
3. (Cancelled)
4. (Previously amended) The method of claim 1 further comprising:
 - generating the PN code at a first chip period; and
 - accepting a second time interval proportionally related to the first chip period.
5. (Original) The method of claim 4 wherein accepting a second time interval includes accepting a second time interval from among a plurality of second time intervals.
6. (Previously amended) The method of claim 5 wherein determining a first time interval from among a plurality of first time intervals includes determining a first time interval from among a plurality of first time intervals that are offset from each other by predetermined periods of time.

7. (Original) The method of claim 6 wherein generating the PN code with the first chip period includes generating a PN code with $(2^N - 1)$ states, and a period m equal to $(2^N - 1)$ times the first chip period;
- wherein determining a first time interval includes selecting a first time interval in the range between zero and m , with a resolution of x ; and
- wherein generating a PN code with a second phase, offset a second time interval from the PN code first phase includes generating a PN code with a second phase that is offset with respect to time in units of x .
8. (Original) The method of claim 7 wherein x is the first chip period.
9. (Original) The method of claim 7 wherein x is equal to the first chip period times q , where q is an integer.
10. (Cancelled)
11. (Currently amended) The method of claim 7 in which a direct sequence spread spectrum (DSSS) receiver with a the memory is included, wherein determining a first time interval includes determining a first time interval in the range between x and nx ; and the method further comprising:
- storing n phase-shifting masks in the memory, corresponding to the plurality of first time periods between x and nx ; and
- wherein selecting a phase-shifting mask includes selecting a phase-shifting mask from the n phase-shifting masks stored in the memory.
12. (Currently amended) The method of claim 7 in which a direct sequence spread spectrum (DSSS) receiver with a the memory is included, wherein determining a first time interval includes determining a first time interval from a plurality of first time intervals in the range between x and nx ; and the method further comprising:

storing $\log_2(n)$ phase-shifting masks in the memory corresponding to $\log_2(n)$ intermediate time intervals between x and nx ;
summing intermediate first time intervals to form a first time interval sum;
wherein selecting a plurality of phase-shifting masks includes selecting phase-shifting masks from the memory corresponding to each of the intermediate time intervals in the first time interval sum; and
wherein shifting the PN code first phase with each phase-shifting mask includes shifting the PN code first phase with the phase-shifting masks selected from the memory.

13. (Previously amended) The method of claim 1, wherein the plurality of phase-shifting masks are selected from a number of stored phase-shifting masks, and wherein the number of stored phase-shifting masks is adjustable.

14. (Previously amended) The method of claim 11 in which the DSSS receiver accepts transmissions spread using the first PN code, and in which the DSSS receiver includes a first chip rate clock; the method further comprising:
synchronizing the accepted transmissions with the generated PN code;
following the selecting of a second time interval, powering-off the first chip rate clock during a slotted mode sleep interval;
powering-on the first chip rate clock; and
wherein determining the first time interval includes determining the sleep time interval that the first rate clock was powered-off; and the method further comprising:
following the generating of the PN code with the second phase, resynchronizing the generated PN code with the accepted transmissions.

15. (Currently amended) A receiver, comprising:
a memory ~~having a port to supply~~ arranged to store a plurality of phase-shifting masks at a first time;
a memory port to supply the plurality of phase-shifting masks;

an application means to determine a first time interval, the application means cross-referencing the first time interval to the plurality of phase-shifting masks, the application means having an output connected to the memory port to request the plurality of phase-shifting masks; and

a pseudorandom noise (PN) code generator having a first input connected to the memory to accept the plurality of phase-shifting masks, the PN code generator offsetting a PN code with each phase-shifting mask of the plurality of phase-shifting masks, the PN code generator having an output to supply the PN code with a second phase, offset from the PN code first phase.

16. (Currently amended) The receiver of claim 15 wherein the memory includes a plurality of phase-shifting masks; and

wherein the application means cross-references a plurality of time intervals to the plurality of phase-shifting masks in the memory.

17. (Original) The receiver of claim 16 wherein the PN code generator generates the PN code at a first chip period;

wherein the application means determines a first time interval proportionally related to the first chip period; and

wherein the memory supplies a phase-shifting mask that is offset by a PN code phase shift proportionally related to the first time interval.

18. (Original) The receiver of claim 17 wherein the PN code generator generates the PN code with $(2^N - 1)$ states, and a period m equal to $(2^N - 1)$ times the first chip period;

wherein the application means determines a first time interval from among a plurality of time intervals in the range between zero and m , with a resolution of x ; and

wherein the PN code generator generates a PN code with a second phase, offset from the PN code first phase with a phase shift, expressed as time in units of x .

19. (Original) The receiver of claim 18 wherein x is equal to the first chip period.

20. (Currently amended) The receiver of claim 18 further comprising:
a sleep clock having an output connected to the application means with a period of q times the first chip period, where q is an integer; and
wherein the application means includes a plurality of time intervals ~~have~~ having a resolution of x equal to the sleep clock period.
21. (Original) The receiver of claim 18 wherein the application means includes a plurality of first time intervals in the range between x and nx ; and
the memory includes n phase shift masks corresponding to the plurality of first time periods between x and nx .
22. (Currently amended) The receiver of claim 18 wherein the application means includes a plurality of time intervals in the range between x and nx ;
wherein the application means selects a plurality of $\log_2(n)$ time intervals to form a first interval sum;
wherein the memory includes $\log_2(n)$ phase-shifting masks corresponding to $\log_2(nx)$ intermediate time intervals between x and nx ; and
wherein the application means selects a plurality of phase-shifting masks from the memory corresponding to a plurality of time intervals in the first time interval sum;
wherein the memory supplies the selected phase-shifting masks to the PN code generator;
and
wherein the PN code generator iteratively shifts the PN code first phase with each of the plurality of selected phase-shifting masks to supply the PN code second phase.
23. (Original) The receiver of claim 18 in which transmissions are accepted spread with the PN code, and the receiver further comprising:

a first chip rate clock having an output connected to the PN code generator, the first chip rate clock being powered-off at the beginning of the first time period, and being powered-on at the finish of the first time period; and

a searcher section having an input connected to PN code generator output to accept the PN code with the second phase shift, the searcher section resynchronizing the accepted transmissions with the generated PN code, following the power-on of the first chip rate clock.

24. (Original) The receiver of claim 23 wherein the application means accepts a second time interval corresponding to a slotted sleep mode interval, wherein the application means programs the PN code generator to be powered off for the second time interval; and

wherein the application means determines the first time interval in response to the actual time that the PN code generator was powered-off.

25. (Currently amended) A method for conserving power in a slotted mode of operation, the method comprising:

storing a plurality of phase-shifting masks in a memory at a first time;

generating a synchronized pseudorandom noise (PN) code to despread transmissions;

accepting a slotted mode sleep second time interval from a plurality of second time intervals;

beginning the sleep mode at a first phase of the PN code;

ending the sleep interval;

determining the first time interval between the beginning and the end of the sleep interval; and

selecting a plurality of phase-shifting masks from storage in response to the first time interval;

offsetting the PN code first phase with each phase-shifting mask from the plurality of selected phase-shifting masks;

generating the PN code with a second phase; and

resynchronizing the generated PN code to despread transmissions.